








Industrial relays

Sockets & accessories



G-series		
	Functions F - Delay- ON R - Delay- OFF (+ control contact) Ws - One shot- ON (+ control contact) Wa - One shot- OFF (+ control contact) Wu - One shot- ON Es - Delay- ON (+ control contact) Bp - Flasher, starting OFF Bi - Flasher, starting ON	
	COM-3TP	Turns a general purpose G-series relay into a multifunction timer relay.
Product	Timer module	Weight: 15 gram
Art. no	321 000 205	
Mounting Applicable for... Remarks	Multifunction timer module. Suitable for plug-in in VG-8T and VG-11T sockets. 8 time ranges (0.05s ... 240h), 8 different time functions. Function and time setting by dip-switch for fine-tuning.	

G-series						
						
	VG-8T	VG-11T	CG-1	T-21	VG-8PCB	VG-11PCB
Product	Mounting socket	Mounting socket	Relay retaining clip	Diode module	PCB socket	PCB socket
Art. no	321 000 206	321 000 207	321 000 203	321 000 208	321 000 209	321 000 210
Mounting Applicable for... Remarks Weight Dimensions	DIN rail or wall G08-series relays Screw terminals 59 gram 75 x 38 x 26mm.	DIN rail or wall G11-series relays Screw terminals 62 gram 75 x 38 x 26mm.	on VG- 8T / VG- 11T G08 & G11-relays Metal - -	in VG- 8T / VG- 11T G08 & G11-relays (+A1, -A2) 6 gram 44 x 34 x 15 mm.	PCB G08-series relays 9 gram Ø 28 x 20 mm.	PCB G11-series relays 9 gram Ø 28 x 20 mm.